

01/2011 Trouser with ankle zipper

By: burda style magazine

<http://www.burdastyle.com/projects/012011-trouser-with-ankle-zipp>



Trouser with ankle zipper burda style magazine patterns FAQ

Materials

stretch jersey

Step 1 — Preparation

Größen, Tailles, Sizes				2		3		4				
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	US	Eur.	US	Eur.	US	Eur.	ins	cm	ins	cm	ins	cm
6	32	6	64	6	16	30	76	23	58	32 1/2	82	
8	34	8	68	8	17	31 1/2	80	24 1/2	62	34	86	
10	36	10	72	10	18	33	84	26	66	35 1/2	90	
12	38	12	76	12	19	34 1/2	88	27 1/2	70	37	94	
14	40	14	80	14	20	36 1/2	92	29 1/2	74	38 1/2	98	
16	42	16	84	16	21	37 1/2	96	30 1/2	78	40 1/2	102	
18	44	18	88	18	22	39 1/2	100	32 1/2	82	41 1/2	106	
20	46	20	92	20	23	41	104	34	86	43 1/2	110	
22	48	22	96	22	24	43 1/2	110	36 1/2	92	45 1/2	116	
24	50	24	100	24	25	45 1/2	116	38 1/2	98	48	122	
26	52	26	104	26	26	48	122	41	104	50 1/2	128	
28	54	28	108	28	27	50 1/2	128	43 1/2	110	52 1/2	134	
30	56	30	112	30	28	52 1/2	134	45 1/2	116	55 1/2	140	
32	58	32	116	32	29	55 1/2	140	48	122	57 1/2	146	
34	60	34	120	34	30	57 1/2	146	50 1/2	128	60	152	

Trace the pattern pieces from the pattern sheet. Follow lines and details for views. Lengthen piece 3 as indicated. Trace the pocket piece a second time, but only to lining line (= smaller pocket piece).

The stitching line at the zip slit is \hat{A} -marked for size 36. For sizes 38 \hat{A} — 44, mark the stitching line the same distance from centre front as for size 36, noting length of slit.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), hem 4 cm (15/8 ins).

Step 2 — Cutting out

1 \hat{A} — front trouser piece 2x

2 \hat{A} — large pocket piece 2x

2 \hat{A} — small pocket piece 2x

3 \hat{A} — back trouser piece 2x

4 \hat{A} — back yoke 2x

5 \hat{A} — front waistband 4x

6 \hat{A} — back waistband 4x

a) left underlap piece, 17 \hat{A} — 17 \hat{A} — 17 \hat{A} — 19 \hat{A} — 19 cm (63/4 \hat{A} — 63/4 \hat{A} — 63/4 \hat{A} — 71/2 \hat{A} — 71/2 ins) long, 5 cm (2 ins) wide, finished width 2.5 cm (1 in).

Interfacing: Iron to waistband \hat{A} -pieces.

Step 3 — Front and pleats

Fold front trouser pieces lengthwise, wrong side facing in, and press creases. Fold pleats in upper edge of trousers in direction of arrows and baste.

Step 4 — Yokes

Stitch back yokes to back trouser pieces. Press seam allowances onto yokes.

Step 5 — Side seams

Stitch side seams, not stitching across pocket openings and ending stitching at lower edges about 10 cm (4 ins) above slit marks.

Step 6 — In-seam pockets

Pin pocket pieces right sides together with seam allowances of pocket opening edges \hat{A} — large pocket pieces in back and small pocket pieces in front. Stitch pocket pieces in place, stitching close to side seam and at edge of pocket opening stitching along seam line. Press pocket pieces forward and stitch together. Baste pocket pieces to wrong side of front trouser pieces, first trimming away allowance of right pocket piece along centre front.

Step 7 — Leg seams

Stitch inside leg seams. Stitch centre front seam from slit mark to inside leg seam.

Step 8 — Zip slit

Press self-facings on slit edges, along centre front on the right and 5 mm (3/16 in) before centre front on the left. Stitch zip under left edge of slit (underlap), close to teeth of zip. Pin slit closed, matching centre fronts. Stitch loose zip tape to right facing, not catching trouser piece. Baste facing in place. Topstitch slit as marked, from the top to 3 cm (1 1/4 ins) before the end. Fold underlap piece lengthwise and stitch across bottom end. Turn right side out. Lay underlap under left edge of slit and pin to slit facing. Stitch slit facing to underlap piece, close to zip joining seam. Lay slit closed again and topstitch to the end, catching underlap.

Step 9 — Waistband and centre back seam

Stitch side seams on waistband pieces. Stitch outer waistband unit to upper edges of trousers, leaving right end of waistband extending from centre front and stitching left end of waistband to slit underlap. Press allowances of joining seams onto waistband. Lay inside waistband unit right sides together with attached waistband unit. Stitch upper edges together. Lay inside waistband unit up and stitch to seam allowances, close to seam. Trim right front end of waistband to 1 cm (3/8 in) before centre front. Work a buttonhole in inside right front waistband. Lay inside waistband unit right sides together with outer waistband unit. Stitch across front ends of waistband. Trim seam allowances. Turn waistband right side out. In back, turn inside waistband up again and stitch centre back seam. Press seam open, from upper edge to beginning of curve. Turn in inside edge of waistband, about 3 cm (1 1/4 ins) long, and baste, then lay remaining waistband edge flat over joining seam, without turning in. Work from right side of garment to stitch along joining seam, catching inside edge of waistband.

Step 10 — Zip

Sew invisible zips to side slit edges, from hem line to slit mark. Stitch remainder of each side seam, up to zip.

Step 11 — Hem allowances

Press hem allowances to inside and sew in place by hand.

Step 12 — Creases

Press creases in back trouser pieces. Press creases in front hem edge.

Step 13 — Back yokes

Topstitch back yokes close to joining seams and 7 mm (1/4 in) from these seams. Topstitch waistband close to edges.

BurdaStyle

01/2011 Trouser with ankle zipper