

11/2010 Double breasted blouse

By: burda style magazine

<http://www.burdastyle.com/projects/112010-double-breasted-blous>



Double breasted blouse burda style magazine patterns FAQ

Materials

cotton poplin

Step 1 — Preparation

1	Größen, Tailles, Sizes						2 Oberweite Tour de poitrine Bust ins cm	3 Tailleweite Tour des taille Waist ins cm	4 Hüftweite Tour des hanches Hip ins cm			
	N		L		K							
	US	Eur.	US	Eur.	US	Eur.						
5	6	32	6	64	6	16	30	76	23	58	32 1/2	82
8	34	8	68	8	17	31 1/2	80	24 1/2	62	34	86	
10	36	10	72	10	18	33	84	26	66	35 1/2	90	
12	38	12	76	12	19	34 1/2	88	27 1/2	70	37	94	
14	40	14	80	14	20	36 1/2	92	29 1/2	74	38 1/2	98	
16	42	16	84	16	21	37 1/2	96	30 1/2	78	40 1/2	102	
18	44	18	88	18	22	39 1/2	100	32 1/2	82	41 1/2	106	
20	46	20	92	20	23	41	104	34	86	43 1/2	110	
22	48	22	96	22	24	43 1/2	110	36 1/2	92	45 1/2	116	
24	50	24	100	24	25	45 1/2	116	38 1/2	98	48	122	
26	52	26	104	26	26	48	122	41	104	50 1/2	128	
28	54	28	108	28	27	50 1/2	128	43 1/2	110	52 1/2	134	
30	56	30	112	30	28	52 1/2	134	45 1/2	116	55 1/2	140	
32	58	32	116	32	29	55 1/2	140	48	122	57 1/2	146	
34	60	34	120	34	30	57 1/2	146	50 1/2	128	60	152	

Trace the pattern pieces from the pattern sheet.

The buttonholes and button markings on piece 1 are for size 17. For sizes 18 — 21, mark the top buttonhole the same distance from neck edge as for size 17. The bottom buttonhole is in the same place for all sizes. Space the other buttonholes evenly in between. Remark the button positions to match.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), hem 2 cm (3/4 in).

Step 2 — Cutting out



1 — front 2x

2 — back 2x

3 — sleeve 2x

4 — cuff 2x

5 — back facing, on a fold 1x

a) 2 bias binding strips for sleeve vents, 19 cm (7 1/2 ins) long, 3 cm (1 1/4 ins) wide (incl. allowances).

Interfacing: See pattern layout. Interface outer halves of cuffs.

Step 3 — Bust darts

Stitch bust darts. Trim dart allowances to 7 mm (1/4 in) wide, neaten edges, and press toward centre.

Stitch darts in back pieces and press toward centre.

Step 4 — Back

Stitch centre back seam. Trim seam allowances to 7 mm (1/4 in) wide, neaten together, and press to one side.

Stitch shoulder seams (seam number 1). Press seam allowances onto back. Topstitch close to seams. Stitch side seams.

Step 5 — Self-facings

Lay front self-facings to outside and stitch to back facing. Stitch facing right sides together with neck edge. Trim seam allowances. Lay facing up and stitch to seam allowances, as far as possible, close to seam. Turn facing to inside and press edges.

Step 6 — Hem

Unfold facings at hem. Lay hem allowance to inside, turn in, and stitch 1 cm (3/8 in) from lower fold edge. Lay facings to inside again and sew to hem allowance.

Step 7 — Sleeve vents

Slash sleeve vents as marked. Spread slash edges apart to a straight line and stitch to one lengthwise edge of each binding strip, as narrowly as possible. Press binding strip over joining seam into vent, then turn in to a width of 7 mm (1/4 in). On inside, stitch fold edge of binding along joining seam. Mitre binding at top of vent, from inside. Lay binding at front edge of each vent to inside and baste at lower edge.

Step 8 — Sleeves

Stitch sleeve seams. Fold pleats in lower edges of sleeves in direction of arrows and baste.

Step 9 — Cuffs

Stitch cuffs to lower edges of sleeves. Press seam allowances of joining seams and of other long edges of cuffs onto cuffs. Fold each cuffs along fold line, right side facing in. Stitch across side edges. Turn right side out. Baste inside edges in place. Topstitch cuffs close to joining seams.

Step 10 — Sleeve caps

Set in sleeves, easing sleeve caps.

Step 11 — Buttonholes

Work buttonholes in right front and in cuffs. Work top buttonhole in left front, for inside button.

BurdaStyle

11/2010 Double breasted blouse