

02/2011 Safari waistcoat with pockets

By: burda style magazine

<http://www.burdastyle.com/projects/022011-safari-waistcoat-with-p>



Safari waistcoat with pockets burda style magazine patterns FAQ

Materials

cotton poplin with crosswise stretch

Step 1 — Preparation

Größen, Tailles, Sizes						2		3		4		
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	5'6" 168 cm		5'9" 176 cm		5'3" 160 cm		ins	cm	ins	cm	ins	cm
	US	Eur.	US	Eur.	US	Eur.						
	6	32	6	64	6	16	30	76	23	58	32 ½	82
	8	34	8	68	8	17	31 ½	80	24 ½	62	34	86
	10	36	10	72	10	18	33	84	26	66	35 ½	90
	12	38	12	76	12	19	34 ½	88	27 ½	70	37	94
	14	40	14	80	14	20	36 ½	92	29 ½	74	38 ½	98
	16	42	16	84	16	21	37 ½	96	30 ½	78	40 ½	102
	18	44	18	88	18	22	39 ½	100	32 ½	82	41 ½	106
	20	46	20	92	20	23	41	104	34	86	43 ½	110
	22	48	22	96	22	24	43 ½	110	36 ½	92	45 ½	116
	24	50	24	100	24	25	45 ½	116	38 ½	98	48	122
	26	52	26	104	26	26	48	122	41	104	50 ½	128
	28	54	28	108	28	27	50 ½	128	43 ½	110	52 ½	134
	30	56	30	112	30	28	52 ½	134	45 ½	116	55 ½	140
	32	58	32	116	32	29	55 ½	140	48	122	57 ½	146
	34	60	34	120	34	30	57 ½	146	50 ½	128	60	152

Trace the pattern pieces from the pattern sheet. Note different hem lines for views A and B.

The snap fasteners marked on pieces 1 and 2 are for size 34. For sizes 36 — 42, mark the top snap fastener the same distance from neck edge as for size 34. The bottom snap on piece 1 is the same for all sizes.

Space the other snaps evenly in between. On piece 2, mark one snap for view A and three snaps for view B, spaced as above.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), hem 4 cm (15/8 ins).

Step 2 — Cutting out



Beige fabric:

1 — upper front 2x

2 — lower front 2x

3 — upper back, on a fold 1x

4 — lower back 2x

6 — back facing, on a fold 1x

7 — flap (upper pocket) 4x

8 — upper pocket 2x

9 — flap (lower pocket) 4x

10 — lower pocket 2x

a) 4 tab pieces (shoulder), 14.5 — 14.5 — 15 — 15 — 15.5 cm (5³/₄ — 5³/₄ — 6 — 6 — 6¹/₄ ins) long, 4 cm (1⁵/₈ ins) wide,

b) tie belt (view A), 130 — 135 — 140 — 140 — 145 cm (51 — 53 — 55 — 55 — 57 ins) long, 5 cm (2 ins) wide, finished width 2.5 cm (1 in).

White fabric:

5 — armhole band 2x

Interfacing: See pattern layout.

Step 3 — Pleat

For the inverted pleat at centre back, fold upper back piece so that pleat lines meet, right side facing in. Stitch pleat from upper edge to arrow mark and baste below mark. Unfold back. Lay pleat in direction of arrow and press. Baste pleat to neck edge and lower edge. Stitch centre seam of lower back. Press seam allowances open. Lay pleat in direction of arrows and press. Baste pleat to upper edge.

Step 4 — Darts

Stitch front and back darts. Press darts toward centre. Stitch upper fronts to lower front and stitch upper back to lower back. Press seam allowances up. Topstitch upper pieces close to seam.

Step 5 — Side seams

Stitch side seams and shoulder seams.

Step 6 — Hem

Press hem allowance to inside and stitch 3 cm (1 1/4 ins) from lower fold edge. Press pleat folds in hem.

Step 7 — Pockets

Fold pockets at centre so that pleat lines meet, right side facing in. Stitch each pleat from upper edge to arrow mark and baste below mark. Unfold pockets. Press pleats. Undo basting. Baste pleats to upper and lower edges of pockets. Lay self-facing on upper edge of each pocket to inside and stitch 2.5 cm (1 in) from fold. Press remaining pocket allowances to wrong side. Topstitch close to side pocket opening edges of lower pockets, then topstitch again 1 cm (3/8 in) from edges. Stitch pockets to fronts at placement lines.

Step 8 — Upper and lower flaps

Stitch each interfaced flap piece to a flap piece with no interfacing, right sides together, leaving joining edge open. Turn right side out. Topstitch close to edges and again 7 mm (1/4 in) from edges. Trim allowances at joining edges to 7 mm (1/4 in) wide. Stitch upper flaps in place, 1.5 cm (5/8 in) above upper pockets. Stitch lower flaps in place, 2.5 cm (1 in) above lower pockets. Press flaps down and stitch again 7 mm (1/4 in) from joining seams. Topstitch flaps close to edges and again 1 cm (3/8 in) from edges. Stitch flaps in place, 2 cm (3/4 in) above pockets.

Step 9 — Self-facings

Lay self-facings on both fronts to outside and stitch to back facing. Stitch facing to neck edge. Trim seam allowances. Turn facing to inside and press edges. Sew facings to hem allowance. Sew inside edge of facing to seams.

Step 10 — Shoulder tabs

Lay each interfaced tab piece on a tab piece with no interfacing, right sides together. Trim one end of each tab to a point. Stitch along lengthwise edges and pointed end of tabs. Turn right side out. Topstitch tabs. Lay tabs on shoulder seams and baste to armhole edges. Fasten shoulder tabs to shoulder seams with one snap each, not catching facing.

Step 11 — Bands

Stitch narrow edges of each armhole band together. Fold bands on fold line, wrong side facing in, and press. Stitch edges of each band together to armhole edges, matching seam of band with side seam. Fold bands in half to outside.

Step 12 — Snap fasteners

Attach snap fasteners to fronts with top halves of snaps on the right and bottom halves on the left. Make thread loops, about 3 cm (1 1/4 ins) long, over waist seam at side seams. For each thread loop, stretch 3— 4 threads and cover them closely with buttonhole stitches.

Step 13 — Tie belt

Fold tie belt lengthwise, right side facing in. Trim ends at an angle. Stitch edges together, leaving a small piece of seam open for turning. Turn belt right side out and sew opening closed. Topstitch belt close to edges.

BurdaStyle

02/2011 Safari waistcoat with pockets