

10/2011 Bootcut flannel trousers

By: burda style magazine

<http://www.burdastyle.com/projects/102011-bootcut-flannel-trousers>



Flannel trousers burda style magazine patterns FAQ

Materials

Flannel

Step 1 — Preparation



Paper cut for ANSI A (German DIN A4) prints:

This pattern is printed on 8.5 × 11 sheets of plain paper. Do not scale or center pages before printing. Wait until all sheets are printed out before beginning to tape them together. **Do not cut out pattern pieces yet**— Arrange the sheets on a large, hard, flat surface so that they fit together, matching up like numbers and letters (i.e. 6A to 6A). To tape pattern together, fold under the margin of one piece (6A) and tape right against the line of it's matching number/letter (6A).

burda style magazine pattern do not have seam allowance included.

Seam and hem allowances to be added: Seams and edges 1.5 cm (5/8 in).

Step 2 — Cutting out



Flannel:

21 front trouser piece 2x

22 back trouser piece 2x

23 pocket 2x

24 waistband 4x

a) left underlap piece, 15 cm — 15 cm — 15 cm — 17 cm — 17 cm long, 6 cm (2 1/2 ins) wide, finished width 3 cm (1 1/4 ins),

b) 4 bias welt strips, 17 cm (6 3/4 ins) long, 4 cm (1 5/8 ins) wide (incl. allowances).

Lining: piece 23.

Interfacing: See pattern layout.

Step 3 — Stretch seam edges

Lay the back trouser pieces right sides together. Press inside leg edges above marking, with a steam-iron or under a damp cloth, until they match corresponding edges of front trouser pieces.

Step 4 — Darts

Stitch back darts and press toward centre back.

Step 5 — Pockets

Mark an abutting line for each welt, 1 cm (3/8 in) from welt joining lines (= finished width of welts). Hand-baste along these lines to match them visible on right fabric side. Fold welt strips lengthwise, right side out. Baste folded welt strips to pockets so that fold edge meets abutting line. Stitch welts in place along welt joining lines. Slash between lines of stitching and clip diagonally toward front ends of seams, not cutting into welts. Turn welts toward pocket opening and press. Lay fold edges of welts together and baste together with herringbone stitch. Fold small triangle at front ends of pocket openings to inside and stitch to welts, from seam end to seam end. Lay each lining piece on pocket piece of outer fabric, right sides together. Stitch edges together, leaving side edges open. Turn pockets right side out. Press edges. Pin lining in place, above and below welted edges of pockets. Cut lining in centre of pocket opening, to 1 cm (3/8 in) before front edge of opening, then clip diagonally toward ends of welt joining seams. Turn in edges of lining and sew to welt joining seams and to front pocket opening ends. Pin pockets to trouser fronts, at abutting lines. Edgestitch pockets in place and baste side edges of pockets in place.

Step 6 — Side seams

Stitch side seams and inside leg seam. Press seam allowances open. Stitch the centre front seam from the slit mark to the inside leg seam.

Step 7 — Zip

Zip opening: Press self-facings on opening edges to inside. On right edge, stitch along centre front. On left edge, stitch 5 mm (3/16 in) before centre front. Stitch zip under left edge of opening (underlap), close to teeth of zip. Pin opening closed, matching centre fronts. Stitch loose zip tape to right facing, not catching trouser piece. Baste facing in place. Topstitch opening from top to 3 cm (1 1/4 ins) before end, as marked. Fold underlap piece lengthwise. Stitch across bottom end. Turn right side out. Lay underlap under left opening edge and pin to facing. Stitch facing to underlap, close to zip joining seam. Lay opening closed again and topstitch to the end, catching underlap.

Step 8 — Waistband

Waistband and centre back seam, see style 137. Omit side seams on waistband. Attach only one trouser hook to waistband.

Step 9 — Hem

Press hem allowances to inside and sew in place by hand.

BurdaStyle

10/2011 Bootcut flannel trousers