

# 01/2011 Skirt with front pleats

By: burda style magazine

<http://www.burdastyle.com/projects/012011-skirt-with-front-pleats>

---



Skirt with front pleats burda style magazine patterns FAQ

## Materials

flannel

---

## Step 1 — Preparation

Größen, Tailles, Sizes						2		3		4		
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	5'6" 168 cm		5'9" 176 cm		5'3" 160 cm		ins	cm	ins	cm	ins	cm
	US	Eur.	US	Eur.	US	Eur.						
	6	32	6	64	6	16	30	76	23	58	32 ½	82
	8	34	8	68	8	17	31 ½	80	24 ½	62	34	86
	10	36	10	72	10	18	33	84	26	66	35 ½	90
	12	38	12	76	12	19	34 ¾	88	27 ¾	70	37	94
	14	40	14	80	14	20	36 ¾	92	29 ¾	74	38 ¾	98
	16	42	16	84	16	21	37 ¾	96	30 ¾	78	40 ¾	102
	18	44	18	88	18	22	39 ½	100	32 ½	82	41 ¾	106
	20	46	20	92	20	23	41	104	34	86	43 ½	110
	22	48	22	96	22	24	43 ½	110	36 ¾	92	45 ¾	116
	24	50	24	100	24	25	45 ¾	116	38 ¾	98	48	122
	26	52	26	104	26	26	48	122	41	104	50 ½	128
	28	54	28	108	28	27	50 ½	128	43 ½	110	52 ¾	134
	30	56	30	112	30	28	52 ¾	134	45 ¾	116	55 ¾	140
	32	58	32	116	32	29	55 ¾	140	48	122	57 ½	146
	34	60	34	120	34	30	57 ½	146	50 ½	128	60	152

Trace the pattern pieces from the pattern sheet.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), no allowance at hem edges.

---

## Step 2 — Cutting out



Flannel:

21 front yoke, on a fold 1x

22 back yoke, on a fold 1x

23 skirt panel, on a fold 2x

Lining: pieces 21 and 22.

Interfacing: See pattern layout. Also iron a strip of interfacing, about 2 cm (3/4 in) wide, to wrong side of each skirt panel, over mark slash.

---

### **Step 3 — Skirt panels**

Slash skirt panels along centre front and centre back, to seam marks. Spread edges of each slash apart and stitch to lower edge of corresponding yoke, 5 mm (3/16 in) from edge, tapering stitching as narrowly as possible toward end of slash. Press seam allowances onto skirt panels. Topstitch skirt panels close to seams.

---

### **Step 4 — Side seam**

Stitch right side seam.

---

### **Step 5 — Zip**

Sew invisible zip to left side edges of skirt. Stitch left side seam from lower edge to zip.

---

## Step 6 — Yoke lining

Stitch right side seam of yoke lining as mirror image of skirt yoke.

---

## Step 7 — Upper edge of skirt

Pin yoke lining right sides together with upper edge of skirt. At zip slit, turn lining back, about 5 mm (3/16 in) before edge of opening, and pin to upper edge. Lay allowances on edges of skirt slit to outside and pin to upper edge of skirt, over lining. Stitch along upper edge of skirt. Turn allowances at edges of slit to inside. Lay lining up and stitch to seam allowances, as far as possible, close to seam. Turn lining to inside and sew to zip tapes.

---

## Step 8 — Yoke

Sew lower edge of yoke lining to skirt attachment seams.

---

## Step 9 — Lower edge

Neaten lower edge of skirt with an overlock stitch or with zigzag stitch.

---

**BurdaStyle**

01/2011 Skirt with front pleats