

# 10/2011 Dress with galloon lace detail

By: burda style magazine

<http://www.burdastyle.com/projects/102011-dress-with-galloon-lace>

---



Dress with galloon lace detail: Galloon lace is a double edge lace with a usable border on both sides that can be separated for matching border trim. burda style magazine patterns FAQ

## Materials

Wool crpe

---

## Step 1 — Preparation



Paper cut for ANSI A (German DIN A4) prints:

This pattern is printed on 8.5 × 11 sheets of plain paper. Do not scale or center pages before printing. Wait until all sheets are printed out before beginning to tape them together. **Do not cut out pattern pieces yet**— Arrange the sheets on a large, hard, flat surface so that they fit together, matching up like numbers and letters (i.e. 6A to 6A). To tape pattern together, fold under the margin of one piece (6A) and tape right against the line of it's matching number/letter (6A).

Trace the pattern pieces from the pattern sheet, follow lines for the respective sizes.

The sizes for this dress is 76, 80, 84, 88, 92.

76 / EUR 38 / US 8

80 / EUR 40 / US 10

84 / EUR 42 / US 12

88 / EUR 44 / US 14

92 / EUR 46 / US 16

**burda style magazine pattern do not have seam allowance included.**

Seam and hem allowances to be added: Seams and edges 1.5 cm (5/8 in).

---

## Step 2 — Cutting out



Cut the following pieces:

Main fabric:

Pattern piece number 1 – Center front piece, cut on fold x1

Pattern piece number 2 – Side front piece, cut x2

Pattern piece number 3 – Center back piece, cut x2

Pattern piece number 4 – Side back piece, cut x2

Pattern piece number 5 – Sleeve, cut x2

Pattern piece number 6 – Front neck facing, cut x2

Pattern piece number 7 – Back neck facing, cut x2

Lining:

Pattern piece number 1 – Center front piece, cut on fold x1

Pattern piece number 2 – Side front piece, cut x2

Pattern piece number 3 – Center back piece, cut x2

Pattern piece number 4 – Side back piece, cut x2

Interfacing:

Cut pieces for and iron onto all facing pieces.

---

### **Step 3 — Zipper**

Sew invisible zipper to centre back pieces. Stitch centre back seam from lower edge to zipper.

---

### **Step 4 — Front and back**

Lay the side front pieces (piece number 2), right sides facing in, on the center front piece (piece 1) and pin and stitch along the seams (seam number 1, marked on pattern). Press seam allowances open.

Line up the side seams on the center back pieces (piece 3, seam number 2) with the seam (number 2) on the back side pieces (piece number 4). Pin together and stitch. Press seam allowances open.

Now take the joined together complete front piece and lay the back pieces, right sides facing in, on it. Line up shoulder seams and side seams, pin and stitch together. Begin and end stitching on shoulder seams at marked neck edge.

Press seam allowances open.

---

### **Step 5 — Facings**

Lay front facing pieces on front lining pieces with wrong side facing right side of front piece. Tack the pieces in place. Do the same with back facing to back lining pieces. Stitch lower facing edges in place with zigzag stitching.

Stitch the seams of lining in the same way as with the front and back pieces in step 4.

---

### **Step 6 — Neck edge**

Pin facing with lining right sides together with the neck edge of dress. At zipper opening, turn facing back, approx. 5 mm (3/16 in) before edge of opening, and pin to neck edge. At opening edges of dress, turn allowances to outside and pin to neck edge, over facing. Stitch along neck edge. Trim seam allowances. Turn facing up and stitch to seam allowances, as far as possible, close to seam. Turn facing with lining to inside and turn allowances at opening edges to inside. Sew facing and lining to zipper tapes. Tack lining to armhole edges.

---

### **Step 7 — Sleeve**

Lay sleeves inside out, right sides facing in, and pin and stitch the sleeve seams. Press seam allowance open. Fold the sleeve hem allowance to inside, press and stitch in place by hand. .

---

### **Step 8 — Sleeve caps**

Turn the garment inside out and set in sleeves in each armhole, right sides facing each other, easing sleeve caps. Pin down and stitch around the armhole opening. Turn garment back to the right side and press the armhole seam, pressing the allowance out into the sleeve. .

---

### **Step 9 — Galoon lace**

Centre galoon lace on front, approx. 10 cm (4 ins) below neck edge. Angle the lace slightly downward toward left side (see illustration). Trim lace at hem edge of dress, following lace pattern. Sew lace in place by hand. From the remaining lace, cut a longer piece, approx. 45 cm (18 ins) long, and a shorter piece, following the lace pattern. Sew the longer piece to right half of dress, from the waist down. Sew the shorter piece of

lace to left half of dress, further below.

---

## **Step 10 — Hem**

Fold hem allowance of dress to inside, press and stitch in place by hand.  
Hem the lining so that it is approx. 2 cm (3/4 in) shorter than the dress.

---

**BurdaStyle**

10/2011 Dress with galloon lace detail