

09/2011 Striped top

By: burda style magazine

<http://www.burdastyle.com/projects/092011-stripped-top>



Striped top burda style magazine patterns FAQ

Materials

Hoop-striped jersey

Step 1 — Preparation



Text for instructions Step 1:

Paper cut for ANSI A (German DIN A4) prints:

This pattern is printed on 8.5 × 11 sheets of plain paper. Do not scale or center pages before printing. Wait until all sheets are printed out before beginning to tape them together. **Do not cut out pattern pieces yet**— Arrange the sheets on a large, hard, flat surface so that they fit together, matching up like numbers and letters (i.e. 6A to 6A). To tape pattern together, fold under the margin of one piece (6A) and tape right against the line of it's matching number/letter (6A).

burda style magazine pattern do not have seam allowance included.

Seam and hem allowances to be added: Seams and edges 1.5 cm (5/8 in).

see example here: <http://www.burdastyle.com/projects/072011-jumpsuit/instructions/1>

Step 2 — Cutting out



21 front with integrated sleeve,

â—'on a fold 1x

22 back with integrated sleeve,

â—'on a fold 1x

a) facing strip for neck edge, 49 â— 50 â— 51 â— 52 â— 53 cm (19 1/4 â— 19 3/4 â— 20 1/4 â— 20 1/2 â— 21 ins) long, 4 cm (15/8 ins) wide (incl. allowances).

Step 3 — Note

Stitch seams on stretch fabrics with a special stretch stitch or with narrow zigzag stitch. Stitch hems with a twin machine needle to keep them elastic.

Step 4 — Shoulders

Stitch shoulder seams and top sleeve seams as continuous seams. Stitch side seams and sleeve seams as continuous seams. Neaten seam allowances together and press onto back.

Step 5 — Neck edge

Fold facing strip for the neck edge lengthwise, right side out. Press. Pin folded strip to neck edge so that fold edge of strip lies on garment piece, 1 cm (3/8 in) past seam line. Turn in ends of facing strip. Stitch along marked neck edge. Trim seam allowances. Turn facing strip to inside and press edge. Work from right side to topstitch neck edge with the twin needle.

Step 6 — Hem

Turn hem allowances of T-shirt and sleeves to inside. Stitch from right side with the twin needle — 3.5 cm (1 1/2 ins) from lower front and back edges and 4.5 cm (1 7/8 ins) from lower sleeve edges.

BurdaStyle

09/2011 Striped top