

02/2011 Three quarter sleeve blouse

By: burda style magazine

<http://www.burdastyle.com/projects/022011-three-quarter-sleeve-blouse>



Three quarter sleeve blouse burda style magazine patterns FAQ

Materials

poplin

Step 1 — Preparation

Größen, Tailles, Sizes						2		3		4		
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	5'6" 168 cm		5'9" 176 cm		5'3" 160 cm		ins	cm	ins	cm	ins	cm
	US	Eur.	US	Eur.	US	Eur.						
	6	32	6	64	6	16	30	76	23	58	32 ½	82
	8	34	8	68	8	17	31 ½	80	24 ½	62	34	86
	10	36	10	72	10	18	33	84	26	66	35 ½	90
	12	38	12	76	12	19	34 ¾	88	27 ¾	70	37	94
	14	40	14	80	14	20	36 ¾	92	29 ¾	74	38 ¾	98
	16	42	16	84	16	21	37 ¾	96	30 ¾	78	40 ¾	102
	18	44	18	88	18	22	39 ½	100	32 ½	82	41 ¾	106
	20	46	20	92	20	23	41	104	34	86	43 ½	110
	22	48	22	96	22	24	43 ½	110	36 ¾	92	45 ¾	116
	24	50	24	100	24	25	45 ¾	116	38 ¾	98	48	122
	26	52	26	104	26	26	48	122	41	104	50 ¾	128
	28	54	28	108	28	27	50 ½	128	43 ½	110	52 ¾	134
	30	56	30	112	30	28	52 ¾	134	45 ¾	116	55 ¾	140
	32	58	32	116	32	29	55 ¾	140	48	122	57 ¾	146
	34	60	34	120	34	30	57 ¾	146	50 ¾	128	60	152

Trace the pattern pieces from the pattern sheet. Follow lines and details for styles 110 B.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in); hem 2 cm (3/4 in); sleeve hems A 3.5 cm (1 1/2 ins), B 2 cm (3/4 in).

Step 2 — Cutting out



- 1 front 2x
- 2 back, on a fold 1x
- 3 yoke, on a fold 2x
- 4 sleeve 2x
- 5 collar, on a fold 2x

Step 3 — Bust darts

Stitch bust darts. Press darts down.

Step 4 — Yoke

Pin one yoke piece to right fabric side of upper back edge and one yoke to wrong fabric side. Stitch yokes in place and press up. Stitch outer yoke to upper edge of fronts. Press seam allowances onto yoke. Turn in edge of inside yoke and sew to joining \hat{A} -seams. Baste open edges together.

Step 5 — Sides

Stitch side seams. Press hem allowance to inside, turn in, and stitch.

Step 6 — Self-facings

Trim allowance on inside edges of front self-facings to 7 mm (1/4 in) wide and neaten edges. Press these allowances to wrong side and stitch.

Step 7 — Collar and neck edge

Stitch collar pieces right sides together along outer edges, from seam number 3. Trim seam allowances. Turn collar right side out and press. Stitch undercollar to neck edge of yoke. Baste top collar and undercollar pieces together to front neck edges, from front yoke joining seams forward. Lay self-facings to outside and stitch to neck edge, over collar. Trim seam allowances. Clip allowances at ends of seams. Turn facings to inside. Press front edges. On blouse back, press allowances of collar joining seam onto collar. Turn in edge of top collar and sew to joining seam. Sew facings to hem and to sea

Step 8 — Sleeves

Stitch sleeve seams above slit mark and below hem line. Press seam allowances open. Turn in sleeve hem allowances and stitch hems 1 cm (3/8 in) wide

Step 9 — Sleeves

Set in sleeves.

BurdaStyle

02/2011 Three quarter sleeve blouse