

07/2010 Dress with front scarf

By: burda style magazine

<http://www.burdastyle.com/projects/072010-dress-with-front-scarf>

Dress with front scarf This pattern pdf can be used to make the 07/2010 Top with front scarf #114 and the 07/2010 Top with crosswise back straps #115 and includes lines and pattern pieces for these styles as well. burda style magazine patterns FAQ

Materials

fine jersey Note: The fabric used for our original model is so fine that we used a double layer throughout. The inside pieces are referred to as lining pieces in the sewing instructions

Step 1 — Preparation

Trace the pattern pieces from the pattern sheet. Lengthen pieces 21 and 23 as indicated.

Seam and hem allowances:

Seams, edges and hem 1.5 cm (5/8 in).

Step 2 — Cutting out



21 front with integrated strap,

on a fold 2x

22 back, on a fold 2x

23 scarf 2x

a) front loop piece, 12 cm (4 3/4 ins) long, 5 cm (2 ins) wide, finished width 2.5 cm (1 in),

b) 2 loop pieces (straps), 6 cm (2 3/8 ins) long, 8 cm (3 1/4 ins) wide, c) back loop piece, 5 cm (2 ins) long, 8 cm (3 1/4 ins) wide, finished width 4 cm (1 5/8 ins).

Interfacing: See pattern layout. Interface integrated straps to bottom markings.

Vilene Bias Tape: Iron to inside front and back neck edges.

Step 3 — Loop piece

Note: Stitch seams on stretch fabrics with a special stretch stitch or at a narrow zigzag setting. Stitch hems with as twin sewing machine needle to keep them elastic.

Fold back loop piece in half. Stitch lengthwise edges together. Turn loop right side out. Fold loop in half and pin ends together. Baste ends of loop to upper back edge, between markings.

Step 4 — Side seams

Stitch side seams on dress and lining. Trim seam allowances to 7 mm (1/4 ins) wide, neaten together, and press to one side.

Step 5 — Lining and straps

Place lining over dress, with right sides facing. Stitch together along upper edge and along long edges of straps. Lay lining up and stitch to seam allowances, as far as possible, close to seam. Turn lining to inside, and turn straps right side out. Pin ends of straps next to each other under back loop joining seam. Try on dress to check fit of straps. Then stitch straps in place, along line of seam.

Step 6 — Hem Allowances

Lay hem allowances to inside. Stitch in place from right side, with the twin machine needle.

Step 7 — Front loop

Fold front loop in half. Stitch lengthwise edges together. Turn loop right side out. Topstitch loop close to edges. Turn in ends for a finished length of 12 cm (4 3/4 ins). Pin loop to front, at placement line, and edgestitch ends in place.

Step 8 — Scarf and loops

Stitch scarf pieces together. Turn in allowances on all edges of scarf and stitch. Slip scarf through back loop so that seam is centred. Lay ends of scarf forward and slip through front loop. Turn in the 5 cm (2 in) long edges of the loop pieces for the straps, toward each other, for a finished width of 4 cm (15/8 ins), and press. Lay loops around scarf and straps at markings and sew ends together. Gather loops to a width of 2.5 cm (1 in). Sew upper and lower edges to backs of straps.

BurdaStyle

07/2010 Dress with front scarf