

07/2010 Top with crosswise back straps

By: burda style magazine

<http://www.burdastyle.com/projects/072010-top-with-crosswise-back->

Top with crosswise back straps This pattern pdf can also be used to make the 07/2010 Top with front scarf #114 and the 07/2010 Dress with front scarf #113 and includes lines and pattern pieces for these styles as well. burda style magazine patterns FAQ

Materials

hoop-stripped jersey with two-way stretch

Step 1 — Preparation

Trace pattern pieces from pattern sheet.

Seam and hem allowances:

Seams and edges 1 cm (3/8 in), hem 3.5 cm(1 1/2 ins).

Step 2 — Cutting out



21 front with integrated strap,

on a fold 1x

22 back, on a fold 1x

Vilene Bias Tape: Iron onto upper edges of front and back pieces and onto edges of straps.

Step 3 — Side Seams

Stitch side seams. Neaten allowances together and press to one side.

Step 4 — straps

Press allowances on upper edges of front and back and on lengthwise edges of straps to inside. Stitch from right side of fabric, 7 mm (1/4 ins) from edges, with the twin machine needle. Pin back ends of straps under upper back edge. Try on top. Sew straps in place by hand

Step 5 — Hem

Press hem to inside. Stitch hem from right side, 3 cm (1 1/4 ins) wide, with the twin needle.

BurdaStyle

07/2010 Top with crosswise back straps