

01/2011 Three quarter sleeve dress

By: burda style magazine

<http://www.burdastyle.com/projects/012011-three-quarter-sleeve-dress>



Three quarter sleeve dress burda style magazine patterns FAQ

Materials

crpe jersey

Step 1 — Preparation

Größen, Tailles, Sizes						2		3		4		
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	5'6" 168 cm		5'9" 176 cm		5'3" 160 cm		ins	cm	ins	cm	ins	cm
	US	Eur.	US	Eur.	US	Eur.						
	6	32	6	64	6	16	30	76	23	58	32 ½	82
	8	34	8	68	8	17	31 ½	80	24 ½	62	34	86
	10	36	10	72	10	18	33	84	26	66	35 ½	90
	12	38	12	76	12	19	34 ¾	88	27 ¾	70	37	94
	14	40	14	80	14	20	36 ¾	92	29 ¾	74	38 ¾	98
	16	42	16	84	16	21	37 ¾	96	30 ¾	78	40 ¾	102
	18	44	18	88	18	22	39 ½	100	32 ½	82	41 ¾	106
	20	46	20	92	20	23	41	104	34	86	43 ½	110
	22	48	22	96	22	24	43 ½	110	36 ¾	92	45 ¾	116
	24	50	24	100	24	25	45 ¾	116	38 ¾	98	48	122
	26	52	26	104	26	26	48	122	41	104	50 ¾	128
	28	54	28	108	28	27	50 ½	128	43 ½	110	52 ¾	134
	30	56	30	112	30	28	52 ¾	134	45 ¾	116	55 ¾	140
	32	58	32	116	32	29	55 ¾	140	48	122	57 ¾	146
	34	60	34	120	34	30	57 ¾	146	50 ¾	128	60	152

Trace the pattern pieces from the pattern sheet. Follow lines and details for style 108. Lengthen pieces 21, 22, and 23 as indicated.

The buttonholes on piece 22 are \hat{A} -marked for size 36. For sizes 38 \hat{A} — 44, mark the top buttonhole the same distance from upper edge as for size 36. The bottom buttonhole is the same for all sizes. Space the other buttonholes evenly in between.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), hem 4 cm (15/8 ins), front bands and band joining edges 1 cm (3/8 in).

Step 2 — Cutting out



21front 2x

22front band 2x

23back, on a fold 1x

24yoke, on a fold 1x

25sleeve 2x

26collar, on a fold 2x

27collar band, on a fold 2x

a) 2 sleeve bands, 30.5 — 31.5 — 33 — 34 — 35.5 cm (12 — 12³/₈ — 13 — 13¹/₂ — 14¹/₂ ins) long, 14 cm (5¹/₂ ins) wide, finished width 7 cm (2³/₄ ins),

b) 2 bias binding strips for sleeve vents, each 16 cm (6³/₈ ins) long, 3 cm (1¹/₄ ins) wide (incl. allowance).

Interfacing: See pattern layout. Iron Vilene Bias Tape/stay tape to edges of yoke.

Step 3 — Pleat

For the inverted pleat at centre back, fold the back piece so that pleat lines match, right side facing in. Stitch pleat between markings. Baste pleat above and below markings. Unfold back. Lay pleat in direction of arrow and press. Baste pleat to upper edge.

Step 4 — Yokes

Gather upper front edges. Stitch yoke to fronts and to back. Topstitch yoke close to joining seams.

Step 5 — Back pleat

Stitch side seams. Remove basting at back pleat. Press hem allowance to inside, turn in, fold it in direction of arrow and baste to upper back edge. Sew hem by hand.

Step 6 — Front bands

Stitch front bands to fronts. Press allowances of band joining seams and of other long edges of bands onto bands. Fold bands on fold line, right side facing in, and stitch across upper and lower ends. Clip seam allowance of fronts at ends of seams. Turn bands right side out and baste inside edges in place. Topstitch bands close to joining seams.

Step 7 — Collar

Stitch collar band pieces to collar pieces. Trim seam allowances and press open. Stitch collar pieces right sides together along outer edges, beginning and ending stitching exactly on seam line of joining edge. Trim seam allowances. Turn collar right side out and press. Stitch undercollar to neck edge. Turn in inside edge of top collar and baste along joining seam. Topstitch collar close to joining seam.

Step 8 — Sleeve vent

Slash each sleeve vent as marked. Spread cut edges apart to a straight line and stitch as narrowly as possible to one lengthwise edge of binding strip. Press binding strip over joining seam into vent, fold to a width of 7 mm (1/4 in), turn raw edge under, and sew to joining seam. Mitre binding on inside at top of vent. At front edge of vent, lay binding to inside and baste to lower edge.

Step 9 — Pleats

Fold pleats in lower sleeve edges in direction of arrows and baste. Stitch sleeve seams.

Step 10 — Sleeve bands

Stitch sleeve bands to lower sleeve edges. Press allowances of joining seams and of other long edges of sleeve bands onto sleeve bands. Fold sleeve bands half to outside and stitch across ends. Turn sleeve bands right side out. Baste inside edges to joining seams. Topstitch sleeve bands close to joining seams.

Step 11 — Sleeve caps

Set in sleeves, easing sleeve caps.

Step 12 — Buttonholes

Work buttonholes in right front band. Work 2 buttonholes in front end of each sleeve band — 1.5 cm (5/8 in) and 5.5 cm (2 1/4 ins) below joining seam.

01/2011 Three quarter sleeve dress