

5/2011 Cropped Jacket with Lapel Embellishments

By: burda style magazine

<http://www.burdastyle.com/projects/52011-cropped-jacket-with-lapel>



Cropped Jacket with Lapel Embellishments burda style magazine patterns FAQ

Materials

Lightweight denim with width-wide stretch

Step 1 — Preparation

Trace pattern pieces from the pattern sheet. Trace front facing from piece 1 as a separate pattern -piece. The buttons markings on piece 1 are for size 36. For sizes 38 — 44, mark the top button the same distance from upper edge as for size 36. The bottom marking is the same for all sizes. Space the other buttons evenly in between.

The buttonholes on piece 10 are marked for size 36. For the other sizes, remark the buttonholes -according to the size lines.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in).

Step 2 — Cutting Out



- 1— 1centre front with
- 2— integrated back yoke 2x
- 3— 3 front facing 2x
- 4— 2side front 2x
- 5— 3centre back 2x
- 6— 4side back 2x
- 7— 5standing collar, on a fold 2x
- 8— 8upper sleeve 2x
- 9— 9under sleeve 2x
- 10— 10cuff 4x

11 shoulder tab 4x

12 back facing, on a fold 1x

a) 2 back half-belt pieces, 18 $\frac{1}{2}$ — 19 $\frac{1}{2}$ — 20 $\frac{1}{2}$ — 21 $\frac{1}{2}$ — 22 cm (7 $\frac{1}{2}$ — 7 $\frac{1}{2}$ — 8 $\frac{1}{8}$ — 8 $\frac{3}{4}$ ins) long, 5 cm (2 ins) wide,

b) bias strip to bind edge of collar, front edges and hem edge, a total of 230 $\frac{1}{4}$ — 235 $\frac{1}{4}$ — 245 $\frac{1}{4}$ — 250 $\frac{1}{4}$ — 260 cm (90 $\frac{1}{2}$ — 92 $\frac{1}{2}$ — 96 $\frac{1}{2}$ — 98 $\frac{1}{2}$ — 102 $\frac{1}{4}$ ins) long, 4 cm (1 $\frac{5}{8}$ ins) wide (incl. allowances),

c) 2 bias strips to bind sleeve attachment seams 50 $\frac{1}{4}$ — 50 $\frac{1}{4}$ — 55 $\frac{1}{4}$ — 55 $\frac{1}{4}$ — 55 cm (19 $\frac{3}{4}$ — 19 $\frac{3}{4}$ — 21 $\frac{3}{4}$ — 21 $\frac{3}{4}$ — 21 $\frac{3}{4}$ ins) long, 4 cm (1 $\frac{5}{8}$ ins) wide (incl. allowances),

d) 2 bias strips to bind overlap edge of cuffs, 18.5 cm (7 $\frac{1}{4}$ ins) long, 4 cm (1 $\frac{5}{8}$ ins) wide (incl. allowances),

e) 2 bias strips to bind cuff joining seams, 30 $\frac{1}{4}$ — 30 $\frac{1}{4}$ — 35 $\frac{1}{4}$ — 35 $\frac{1}{4}$ — 35 cm (12 $\frac{1}{4}$ — 12 $\frac{1}{4}$ — 13 $\frac{3}{4}$ — 13 $\frac{3}{4}$ ins) long, 4 cm (1 $\frac{5}{8}$ ins) wide (incl. allowances).

Interfacing: See pattern layout. Interface only one of the back half-belt pieces.

Step 3 — Stitch centre back seam

Stitch centre back seam. Press seam allowances onto left back piece. Fold pre-folded bias tape in half lengthwise and press. Lay pre-folded bias tape over seam allowances, pin, and stitch in place. Topstitch left back 7 mm (1/4 in) from seam.

Step 4 — Stitch bust darts

Stitch bust darts. Press darts up. Stitch front section seams. Press allowances onto centre pieces and bind with bias tape. Topstitch centre pieces next to seams. Stitch side seams. Press seam allowances open and bind with bias tape.

Step 5 — Stitch integrated back yokes of front pieces to back piece

Stitch integrated back yokes of front pieces to back piece. Press seam allowances open and bind with bias tape.

Step 6 — Stitch shoulder seams of facing

Stitch shoulder seams of facing. Press seam allowances open. Bind inside edge of facing with bias tape.

Step 7 — Stitch outside collar piece to neck edge of jacket

Stitch outside collar piece to neck edge of jacket and stitch inside collar piece to facing, beginning and ending stitching in front, exactly at seam line on narrow edge of collar. Press seam allowances open. Lay facing wrong sides together with jacket and lay collar pieces together. Pin collar joining seams together. Lay facing up again and stitch seam allowances together, close to collar joining seam. Baste facing to front edges and to hem edge, approx. 2 mm (a scant 1/8 in) from seam allowance. Baste collar pieces together along outer edges, next to seam allowances. Trim away seam allowances around the edges.

Step 8 — Bind edges of jacket

Stitch pieces for binding strip together to one long strip. Fold binding strip in half lengthwise and press, right fabric side facing out. Unfold strip out flat again. Now turn each lengthwise edge of strip in to the pressed crease and press again. Lay binding strip over edges of jacket (hem, front edges and collar) and pin. Baste -binding in place. Stitch from right side of garment, thereby catching inside edge. Begin at one side seam and turn in end of strip.

Step 9 — Integrated Lapels

Fold integrated lapels of front pieces to outside, on fold line, and press. Sew on buttons as marked, catching facing on inside.

Step 10 — Shoulder tabs

Lay each interfaced tab piece on a tab piece with no interfacing, right sides together. Trim one end of each tab to a point. Stitch along lengthwise edges and pointed end of tabs. Turn right side out. Topstitch tabs 7 mm (1/4 in) wide. Lay tabs on shoulder seams and baste to armhole edges. Fasten shoulder tabs to shoulder seams with one snap each, not catching facing.

Step 11 — Stitch back sleeve seams

Stitch back sleeve seams. Press seam allowances onto upper sleeves and bind with bias tape. Topstitch seams. Stitch front sleeve seams. Press seam allowances open and bind with-bias tape.

Step 12 — Cuffs

Lay each interfaced cuff piece on cuff piece with no interfacing, right sides together. Stitch along side edge, next to abutting line, and along lower edge. Turn cuffs right side out and press edges. Baste open side edges together, next to seam allowance. Trim away seam allowances. Bind side edges with bias strips, -turning bottom end of binding to inside and sewing it closed. Work buttonholes as marked. Lay front edges of cuffs (with buttonholes) on back edges, to abutting line, and baste in place. Stitch cuffs to lower edges of sleeves, with wrong sides facing, matching bound edge of cuff to back sleeve seam (seam number 9). Trim seam allowances of joining seams to 1 cm (3/8 in) wide and bind with bias strips, beginning and ending at lower sleeve seam and turning in end of binding strip.

Step 13 — Sleeve caps

Ease sleeve caps and baste sleeves to edges of armholes with wrong sides facing. Stitch sleeves in place. Trim seam allowances of sleeve attachment seams to 1 cm (3/8 in) wide and bind with bias strips.

Step 14 — Half-belt

Lay back half-belt pieces together, right sides facing. Stitch edges together, leaving a section of seam open for turning. Trim seam allowances. Turn half-belt right side out and press edges. Sew seam opening closed. Topstitch half-belt. Work a buttonhole in each end of half-belt. Lay half-belt on back of jacket, -above marked waist line, and button in place.

BurdaStyle

5/2011 Cropped Jacket with Lapel Embellishments