

07/2010 Tunic Top with frills

By: burda style magazine

<http://www.burdastyle.com/projects/072010-tunic-top-with-frills>

Tunic Top with frills burda style magazine patterns FAQ

Materials

batiste

Step 1 — Preparation

Trace pattern pieces from the pattern sheet. Trace the top frill from piece 6 as a separate pattern piece.

Seam and hem allowances:

Seams, edges and hem 1.5 cm (5/8 in).

Step 2 — Cutting out



Batiste

1 front yoke, on a fold 2x

2 front, on a fold 2x

3 back yoke, on a fold 2x

4 back, on a fold 2x

6 top armhole frill 2x

6 bottom armhole frill 2x

Tulle:

1 front yoke, on a fold 1x

3 back yoke, on a fold 1x

Step 3 — Tulle yokes

Baste tulle yokes to each respective batiste piece, with wrong side facing right side, and treat as one layer of fabric from now on (= outer yoke pieces). Stitch shoulder seams on outer and inner yoke layers. Lay outer and inner yoke layers right sides facing and stitch neck edge edges together. Trim seam allowances and clip curves. Lay inner yoke up and stitch to seam allowances, close to seam. Turn yoke right side out and press edge.

Step 4 — Arm frills

Neaten outer edge of armhole frills with closely spaced zigzag stitching: Press allowance to wrong side of fabric. Work from right side of fabric to stitch along fold edge with small, closely spaced zigzag stitching. Carefully trim allowance on inside, close to stitching. Lay top frills on bottom frills. Baste joining edges together and gather. Stitch frills to armhole edges of outer yoke, above markings.

Step 5 — Armholes

First turn edges of one armhole in toward each other at the side seam and hold with a single pin. Reach between outer and inner yoke layers to pull edges of armhole out. Remove the pin but keep hold of the edges. Work from the side seam edge to stitch edges of armhole right sides together, stitching as far as possible at the top and catching the frill. Trim seam allowances and clip curves. Push seam back in again. Then stitch from the other side seam edge. Push seam back in again. Turn in the still free edge of armhole on inner yoke and sew to frill joining seam. Stitch edge of other armhole in same manner.

Step 6 — Side seams and inner yokes

Stitch each side seam on outer and inner yokes as continuous seam.

Step 7 — Hem allowance

Lay one front and one back piece each right sides together and stitch side seams. Neaten seam allowances together and press onto back. Press hem allowance on one front and back piece to inside, turn raw edge under narrowly, and stitch. Press hem allowance on other piece to inside, 2 cm (3/4 in) wider than marked. Trim hem allowance to 1 cm (3/8 in) wide, turn raw edge under, and stitch. Place shorter front and back over longer front and back with wrong side facing right side. Baste upper edges together and gather.

Step 8 — Yokes

Stitch outer yoke to upper edge of front and back. Turn in edge of inner yoke and sew to joining seam.

Step 9 — Lace insert

Place lace insert on front yoke — bottom end of insert extends past yoke joining seam. Sew insert in place by hand.

BurdaStyle

07/2010 Tunic Top with frills