

01/2011 Wrap top

By: burda style magazine

<http://www.burdastyle.com/projects/012011-wrap-top>



Wrap top burda style magazine patterns FAQ

Materials

wide wool jersey

Step 1 — Preparation

Größen, Tailles, Sizes						2		3		4		
1	N		L		K		Oberweite Tour de poitrine Bust		Tailleweite Tour des taille Waist		Hüftweite Tour des hanches Hip	
	5'6" 168 cm		5'9" 176 cm		5'3" 160 cm		ins	cm	ins	cm	ins	cm
	US	Eur.	US	Eur.	US	Eur.						
	6	32	6	64	6	16	30	76	23	58	32 ½	82
	8	34	8	68	8	17	31 ½	80	24 ½	62	34	86
	10	36	10	72	10	18	33	84	26	66	35 ½	90
	12	38	12	76	12	19	34 ¾	88	27 ¾	70	37	94
	14	40	14	80	14	20	36 ¾	92	29 ¾	74	38 ¾	98
	16	42	16	84	16	21	37 ¾	96	30 ¾	78	40 ¾	102
	18	44	18	88	18	22	39 ½	100	32 ½	82	41 ¾	106
	20	46	20	92	20	23	41	104	34	86	43 ½	110
	22	48	22	96	22	24	43 ½	110	36 ¾	92	45 ¾	116
	24	50	24	100	24	25	45 ¾	116	38 ¾	98	48	122
	26	52	26	104	26	26	48	122	41	104	50 ½	128
	28	54	28	108	28	27	50 ½	128	43 ½	110	52 ¾	134
	30	56	30	112	30	28	52 ¾	134	45 ¾	116	55 ¾	140
	32	58	32	116	32	29	55 ¾	140	48	122	57 ½	146
	34	60	34	120	34	30	57 ½	146	50 ½	128	60	152

Trace the pattern pieces from the pattern sheet.

Seam and hem allowances:

Seams and edges 1.5 cm (5/8 in), hem 2 cm (3/4 in), sleeve hems 6 cm (23/8 ins) (flare sleeve hem allowance).

Step 2 — Cutting out



21front 2x

22back, on a fold 1x

23sleeve 2x

a) facing strip for back neck edge, 18 — 18 — 19 — 19 — 20 cm (7 — 7 — 7 1/2 — 7 1/2 — 8 ins) long, 6 cm (2 3/8 ins) wide (incl. allowance),

b) 2 tie bands, 98 — 100 — 102 — 104 — 106 cm (38 3/4 — 39 1/2 — 40 1/4 — 41 — 41 3/4 ins) long, 10 cm (4 ins) wide, finished width 5 cm (2 ins).

Interfacing: See pattern layout. Iron a shaped strip of interfacing, about 3 cm (1 1/4 ins) wide, to wrong side of each front, next to self-facing. Iron Vilene Bias Tape/stay tape to wrong side of back neck edge. Iron Vilene Bias Tape/stay tape to wrong side of front shoulder edges.

Step 3 — Facings

Fold self-facings on front neck edges to inside on fold line and press. Lay facings forward again. Neaten inside edges with zigzag stitching. Stitch shoulder seams, beginning and ending exactly at marked neck edge. Press seam allowances open.

Step 4 — Facing strip

Fold facing strip for back neck edge lengthwise, right side facing in, and press. Pin folded facing strip to back neck edge so that fold edge of strip lies on garment piece, 1.5 cm (5/8 in) past seam line. Stitch along neck edge. Trim seam allowances. Turn facing strip to inside and press edge. Topstitch 1 cm (3/8 in) from back neck edge.

Step 5 — Sides

Stitch side seams, leaving right slit open. Press seam allowances open and press edges of slit.

Step 6 — Tie band

Fold tie bands lengthwise, right side facing in. Stitch along long edge and across one end of each. Trim seam allowances. Turn tie bands right side out and press. Baste tie bands to narrow front edges.

Step 7 — Neck facings

Now first unfold neck facings and then hem allowance and pin over tie bands. Stitch along front edges. Turn hem allowance and facings to inside. Press hem edge. Turn in top ends of facing and sew to shoulder seams. Sew inside edges of facing in place, loosely, by hand. Work from right side to topstitch 1.5 cm (5/8 in) from hem edge, using the twin machine needle.

Step 8 — Sleeve seams

Stitch sleeve seams. Press sleeve hem allowances to inside. Stitch hems from right side, 5 cm (2 ins) from lower edge, with the twin machine needle

Step 9 — Sleeves

Set in sleeves.

BurdaStyle

01/2011 Wrap top